

International Science Journal[®]
SCIENCE-ENGINEERING-TECHNOLOGY
Scientific Journals

Knowledge Drives Us, Science Unites Us.

**Join us in this issue as we explore the discoveries that are redefining
our world.**

**From the bold innovations of today to the transformative ideas of
tomorrow, we reveal how science and technology are shaping
humanity's future.**




Issue 2, Volume 1, No. 02, July-December 2025



International Science Journal

ISSN: 3122-3591



Review International Science Journal ISSN: 3122-3591 Issue 2, Volume 1, No. 02, July-December 2025

Issue 2, Volume 1, No. 02, July-December 2025

3D Printing and Regenerative Medicine in Orthopedic Trauma Reconstruction

Diego Arath Torres Garrido

Independiente

datg2103@gmail.com

<https://orcid.org/0009-0001-7416-453X>

Juan Diego Paloma Meza

Independiente

juandiegopaloma@outlook.com

<https://orcid.org/0009-0007-8879-3496>

Antonio Cueva Pérez

Universidad Autónoma de Guadalajara

antonio.cueval@hotmail.com

<https://orcid.org/0009-0004-5018-6875>

Daniela Lisseth Herrera Santillán

Independiente

dh.herrera.santillan@gmail.com

<https://orcid.org/0000-0003-1153-0245>

Jacobo Restrepo Gómez

Universidad de Manizales

rjacob0828@gmail.com

<https://orcid.org/0009-0006-7703-7479>

Maximiliano Cueva Pérez

Universidad Autónoma de Guadalajara

maxcueva2005@gmail.com

<https://orcid.org/0009-0003-4123-2983>

Jhon Jairo Fernández Rendón

Universidad de Especialidades Espíritu Santo

j_jairofer@outlook.com

<https://orcid.org/0009-0000-8110-8643>

Luis Cail Veliz Briones

Ministerio de Salud Publica

Cailveliz@gmail.com

<https://orcid.org/0009-0008-7965-8265>

Received: 10-14-2025 | **Accepted:** 10-14-2025 | **Published:** 10-17-2025

* **Corresponding Author:** datg2103@gmail.com

How to cite this article: Torres Garrido, D. A., Paloma Meza, J. D., Cueva Pérez, A., Herrera Santillán, D. L., Restrepo Gómez, J., Cueva Pérez, M., Fernández Rendón, J. J., & Cail Veliz Briones, L. (2025). 3D Printing and Regenerative Medicine in Orthopedic Trauma Reconstruction. México. International Science Journal "TheSci". 2 (1) 30-51. Quality Consulting Instituto de Educación Capacitación y Certificación de México. <https://ieccmexico.com/thesci>

Copyright (c). 2025 Torres Garrido, D. A., Paloma Meza, J. D., Cueva Pérez, A., Herrera Santillán, D. L., Restrepo Gómez, J., Cueva Pérez, M., Fernández Rendón, J. J., & Cail Veliz Briones, L.; This is an open access article distributed under the terms of the Attribution 4.0 International ([CC BY-NC-SA 4.0](https://creativecommons.org/licenses/by-nc-sa/4.0/)) International Science Journal "TheSci". Mexico Review/ Vol. 2, N. 2 / pp. 30-51/ July-December 2025 / e-ISSN: in process / p-ISSN: in process. Research Article

ABSTRACT

Three-dimensional (3D) printing and regenerative medicine have revolutionized orthopedic trauma reconstruction by introducing personalized, biomimetic, and biologically active solutions for complex skeletal injuries. This multicenter study, conducted in Mexico, Colombia, and Ecuador, evaluated the clinical, functional, and radiological outcomes associated with the use of 3D-printed implants and regenerative scaffolds compared to conventional reconstruction techniques. A quantitative, cross-sectional, and analytical design was applied to 128 patients who underwent reconstructive surgery following post-traumatic bone defects. Participants were divided into three groups: 3D-printed implants, regenerative scaffolds with bioactive components, and conventional grafts. Statistical analyses included descriptive and inferential methods, with significance established at $p < 0.05$.

Results demonstrated that patients treated with 3D-printed implants achieved the highest bone healing rate (91–94%), superior functional recovery (LEFS = 88 at 12 months), and the greatest radiological integration index (0.93), while also exhibiting the lowest rates of infection (3.5%), implant failure (2.0%), and nonunion (4.5%). Regenerative scaffolds also yielded favorable outcomes, with healing rates of 85–90% and an integration index of 0.88, confirming their strong osteogenic and angiogenic potential. In contrast, conventional grafts presented inferior results, with higher complication rates (infection 7.5%, nonunion 12%) and lower integration (0.76).

The findings validate the biomechanical and biological advantages of additive and regenerative technologies, demonstrating their feasibility and scalability within Latin American healthcare systems. This study concludes that the combination of 3D printing precision and regenerative bioactivity represents a paradigm shift in trauma reconstruction—offering safer, faster, and more patient-specific therapeutic outcomes that redefine the future of personalized orthopedic medicine.

KEYWORDS

3D printing; regenerative medicine; orthopedic trauma reconstruction; biomaterials; bone regeneration; personalized implants.

INTRODUCTION

Orthopedic trauma reconstruction represents a pivotal challenge in musculoskeletal medicine due to the intricate biological mechanisms underlying bone healing and the limitations of conventional reconstructive procedures. Severe fractures, segmental bone defects, and post-traumatic deformities frequently result in prolonged recovery times and unsatisfactory functional outcomes, particularly when traditional autologous or allogenic grafts fail to provide adequate biomechanical strength or biological integration. The convergence of **three-dimensional (3D) printing** and **regenerative medicine** has revolutionized this field, introducing new possibilities for patient-specific reconstruction, tissue regeneration, and functional restoration [1], [2].

Additive manufacturing, or 3D printing, has evolved from a prototyping technology into a transformative medical tool capable of producing complex, customized structures with unprecedented precision. Its application in orthopedic surgery enables the fabrication of anatomical models, surgical guides, fixation plates, and bioactive scaffolds tailored to the patient's anatomy [3], [4]. Early studies demonstrated how 3D-printed implants can replicate the mechanical and structural features of cortical and cancellous bone, achieving higher levels of integration and reducing complications associated with conventional metallic or polymeric implants [5]. Moreover, the recent introduction of multi-material printers allows simultaneous deposition of polymers, ceramics, and biologically active molecules—broadening the potential of hybrid materials that combine mechanical stability with biological compatibility [6].

Regenerative medicine complements this technological shift by introducing cellular and molecular therapies that enhance osteogenesis and angiogenesis within printed constructs. Bioprinting, an extension of additive manufacturing, employs bioinks containing stem cells, growth factors, and extracellular matrix components to create living tissues with controlled architecture [7], [8]. These advancements have facilitated the design of **biomimetic scaffolds** that recapitulate the hierarchical organization of natural bone and promote cell differentiation and tissue maturation. Wang et al. (2025) demonstrated that novel bioinks integrating polycaprolactone (PCL) with hydroxyapatite nanoparticles improved osteogenic differentiation in vitro and significantly increased mineral deposition in vivo [4]. Similarly, Zhan et al. (2024) described the successful use of calcium phosphate-based bioprinted scaffolds with interconnected porosity, resulting in enhanced vascular infiltration and accelerated bone remodeling [20].

The clinical relevance of these developments extends beyond laboratory innovation. In complex trauma cases—such as comminuted fractures, large bone gaps, or post-infectious reconstructions—3D-printed, patient-specific scaffolds and implants have demonstrated shorter operative times, better anatomical fit, and reduced intraoperative blood loss compared to conventional methods [9], [10]. Calvo-Haro et al. (2021) highlighted how the evolution from *do-it-yourself* printing to *point-of-care manufacturing* has enabled surgeons to design and fabricate implants directly within

hospital environments, transforming preoperative planning and surgical precision [7]. Fidanza et al. (2024) expanded on this perspective, emphasizing the need for economic sustainability and regulatory harmonization to ensure that 3D printing integrates effectively within value-based healthcare frameworks [2].

At the biological level, the synergy between additive manufacturing and regenerative medicine represents a paradigm shift: while 3D printing provides the geometric and mechanical framework, regenerative medicine supplies the biological elements necessary for osteoinduction and osteoconduction. Ansari et al. (2022) and Kanwar and Vijayavenkataraman (2021) demonstrated that scaffold design—particularly pore interconnectivity and surface microtopography—directly influences stem cell behavior, proliferation, and lineage specification [11], [17]. These findings have guided the development of *smart biomaterials* capable of controlled release of signaling molecules and dynamic mechanical adaptation to the healing environment [12], [15].

From a translational standpoint, the integration of 3D printing in trauma reconstruction is also reshaping surgical education, preoperative planning, and patient communication. Wixted et al. (2021) noted that printed anatomical models allow residents to rehearse complex procedures, improving confidence and accuracy during real operations [13]. In addition, the rapid prototyping of guides and implants minimizes human error, facilitating minimally invasive approaches that preserve soft tissues and vascular supply—critical factors for successful bone regeneration [14].

In Latin America, the adoption of additive manufacturing for orthopedic applications has accelerated notably in recent years. Collaborative networks between universities, hospitals, and private industries in **Mexico, Colombia, and Ecuador** have fostered multidisciplinary research in biofabrication, biomechanics, and surgical innovation. Rodríguez-Salvador et al. (2019) identified these countries as regional leaders in bioprinting research, emphasizing their contribution to knowledge transfer and technology democratization [16]. The local production of patient-specific implants has also proven cost-effective in settings where imported prostheses are financially inaccessible, representing a significant step toward healthcare equity [19].

Despite these achievements, several barriers persist. The lack of standardized regulatory frameworks, limited access to high-grade biocompatible materials, and insufficient long-term clinical trials remain major obstacles for full-scale clinical translation [15], [18]. Furthermore, the biological complexity of integrating living tissues with artificial scaffolds continues to demand intensive research in biomechanics, vascular biology, and immune response modulation. Nonetheless, multidisciplinary collaborations among surgeons, engineers, and material scientists continue to close these gaps, progressively bringing personalized bone reconstruction closer to routine clinical practice [5], [10], [12].

This study aims to evaluate the translational impact of 3D printing and regenerative medicine in orthopedic trauma reconstruction across Mexico, Colombia, and Ecuador. Specifically, it investigates the implementation of 3D-printed scaffolds and regenerative biomaterials in the management of complex fractures, their clinical outcomes, and the emerging challenges associated with regulatory and ethical frameworks. The guiding hypothesis posits that integrating additive manufacturing and regenerative therapies improves structural recovery, accelerates functional rehabilitation, and enhances patient-specific outcomes, while simultaneously reducing healthcare disparities in Latin America.

Ultimately, this work contributes to the growing body of literature demonstrating that the convergence of engineering and regenerative sciences is redefining orthopedic trauma care. By contextualizing global advances within regional healthcare systems, the study underscores that 3D printing and regenerative medicine are not merely technological innovations but essential components of a new, patient-centered era in surgical reconstruction [1]–[20].

DEVELOPMENT

The integration of **3D printing and regenerative medicine** in orthopedic trauma reconstruction has evolved from an experimental concept into a rapidly maturing field of translational science. The intersection of engineering, cellular biology, and clinical surgery has made it possible to address long-standing challenges such as delayed union, non-union fractures, and large segmental bone defects that are difficult to treat using conventional grafts or metallic implants [1], [2]. The development of patient-specific 3D-printed scaffolds, in particular, represents a significant milestone, allowing the customization of implant geometry, porosity, and mechanical strength according to the anatomical and biomechanical requirements of each individual case [3], [4].

Recent advances in **additive manufacturing** have refined both the resolution and the biological performance of printed constructs. Through high-precision layer deposition, materials such as titanium alloys, polylactic acid (PLA), polycaprolactone (PCL), and hydroxyapatite composites can be arranged in microarchitectures that replicate the anisotropic and hierarchical structure of human bone [5], [6]. These biomimetic scaffolds not only restore the mechanical load-bearing capacity of the damaged segment but also provide a favorable microenvironment for osteoblast proliferation and vascular infiltration. In a multicenter analysis, Sun et al. (2025) demonstrated that scaffold microtopography and pore interconnectivity directly enhanced osteogenic differentiation, confirming that architectural precision is as crucial as material biocompatibility in promoting bone regeneration [10].

1. Regenerative strategy and biological integration

The biological success of 3D-printed scaffolds depends largely on their ability to promote *osteogenesis* and *angiogenesis*, two essential processes for bone repair. Regenerative medicine contributes to this through the use of **stem cells**, **growth factors**, and **biologically active coatings** that transform inert scaffolds into living, functional constructs [7], [8]. The incorporation of mesenchymal stem cells (MSCs) into printed scaffolds has shown promising results, accelerating new bone formation and reducing fibrotic encapsulation. Kanwar and Vijayavenkataraman (2021) reported that PCL-hydroxyapatite scaffolds seeded with MSCs enhanced mineral deposition by up to 65% compared to acellular controls [17]. Furthermore, controlled release systems embedded within the scaffolds—such as microspheres loaded with bone morphogenetic protein-2 (BMP-2) or vascular endothelial growth factor (VEGF)—have been shown to guide cell differentiation and angiogenesis over time, resulting in faster and more uniform integration with host tissue [9], [12].

These strategies have significant implications for **critical-sized bone defects**, which typically exceed the body's natural healing capacity. Fidanza et al. (2024) described how biofabricated constructs combining mechanical stability with cellular viability have reduced the incidence of postoperative infections and the need for secondary surgeries in trauma patients [2]. Additionally, Liu et al. (2021) demonstrated that bioactive composites printed using extrusion-based bioprinting can maintain viable cell populations and controlled degradation rates, supporting sustained regeneration over several months [9].

2. Clinical applications in trauma reconstruction

From a clinical perspective, 3D printing has been applied in the reconstruction of **long bone defects**, **pelvic fractures**, **maxillofacial injuries**, and **spinal deformities**. In trauma settings, patient-specific implants derived from computed tomography (CT) data provide precise anatomical conformity, minimizing soft-tissue disruption and improving alignment during fixation [13]. Calvo-Haro et al. (2021) highlighted that such approaches significantly reduce intraoperative time—by up to 30%—and blood loss, while improving postoperative recovery rates [7]. In complex pelvic and acetabular fractures, preoperative 3D models allow surgeons to rehearse reduction and fixation procedures, optimizing surgical strategy and minimizing the risk of iatrogenic injury [14].

In the context of **Latin America**, hospitals in Mexico and Colombia have successfully incorporated 3D printing into orthopedic trauma workflows. Studies conducted in Mexico City and Bogotá have demonstrated that locally fabricated guides and implants maintain the same mechanical quality as imported models but at one-third of the cost, improving accessibility in low-resource environments [16]. Rodríguez-Salvador et al. (2019) emphasized that such regional innovation bridges the technological gap in regenerative medicine by enabling independent production of medical devices, fostering both clinical autonomy and economic sustainability [16].

3. Material innovations and mechanical optimization

Material science continues to play a crucial role in the evolution of 3D printing for bone reconstruction. Titanium-based alloys, such as Ti6Al4V, remain the gold standard for load-bearing implants due to their excellent strength-to-weight ratio and biocompatibility. However, polymeric and composite materials have gained prominence for their tunable degradation profiles and ability to host biological components [5], [11]. Ansari et al. (2022) described that hybrid scaffolds combining titanium lattices with biodegradable polymer coatings enhance both mechanical stability and biological integration, effectively reducing stress shielding and improving the mechanical transfer between graft and bone [11].

Emerging biomaterials, including bioactive glasses and ceramic-polymer hybrids, have demonstrated additional regenerative properties by modulating ionic exchange and stimulating osteoinductive pathways [18], [20]. Mirsky and Ghosh (2025) further noted that nanostructured coatings functionalized with peptides and proteins can accelerate osseointegration and promote vascularization in vivo [15]. These developments illustrate a progressive transition from inert implants to **smart biofunctional devices** that actively participate in tissue regeneration rather than merely replacing damaged structures.

4. Challenges and future perspectives

Despite promising advances, several obstacles remain before 3D printing and regenerative medicine become universally adopted in orthopedic trauma care. The lack of regulatory consensus across countries, the variability in material quality, and the absence of long-term randomized clinical trials continue to limit widespread clinical translation [15], [18]. Additionally, ethical considerations concerning bioprinted tissues, intellectual property of patient-specific designs, and biosafety of cellular materials require harmonized guidelines at the international level [2], [7].

However, the trajectory of scientific evidence suggests that these challenges are surmountable. International collaborations are rapidly accelerating progress in this field, supported by multidisciplinary teams of engineers, surgeons, and molecular biologists. In the context of **precision medicine**, the integration of patient data, imaging, and biomechanical modeling enables real-time optimization of printed constructs, ensuring both structural and biological compatibility [1], [10], [14]. The continuous refinement of bioinks, printing resolution, and cell-scaffold interactions promises a future where functional, vascularized bone tissue can be reliably printed and transplanted in clinical settings [4], [6], [8].

Ultimately, the combined use of **3D printing and regenerative medicine** is redefining the landscape of orthopedic trauma reconstruction. Its capacity to merge personalized surgical planning, biomimetic design, and cellular bioactivity positions it as one of the most impactful innovations in modern reconstructive surgery. As ongoing research continues to validate its clinical efficacy, this technology stands to transform trauma care—providing safer, faster, and more accessible solutions for patients worldwide [1]–[20].

GENERAL OBJECTIVE AND SPECIFIC OBJECTIVES

General Objective:

To **analyze, evaluate, and synthesize** the impact of *three-dimensional (3D) printing and regenerative medicine* in the field of **orthopedic trauma reconstruction**, focusing on their clinical, technological, and biological contributions to bone regeneration, personalized implant design, and patient recovery outcomes in Mexico, Colombia, and Ecuador. This study aims to establish a comprehensive understanding of how the integration of additive manufacturing and regenerative strategies enhances surgical precision, accelerates healing, and supports the transition toward personalized, value-based orthopedic care.

Cognitive Domain (Knowledge, Comprehension, Analysis, Evaluation, Creation)

1. **Identify** and describe the fundamental concepts and principles underlying 3D printing and regenerative medicine as applied to orthopedic trauma reconstruction.
2. **Analyze** current international and Latin American research to determine the technological and biological variables that influence bone regeneration outcomes using 3D-printed scaffolds.
3. **Evaluate** the biomechanical performance, cellular response, and integration of bioactive materials within 3D-printed constructs in comparison with traditional reconstruction techniques.
4. **Synthesize** available evidence to propose a conceptual framework for integrating additive manufacturing and regenerative therapies in trauma-related orthopedic rehabilitation.
5. **Create** a multidisciplinary research model that supports innovation, education, and translational application of regenerative orthopedic technologies in developing healthcare systems.

Psychomotor Domain (Skills, Manipulation, Technical Proficiency)

1. **Demonstrate** the ability to interpret imaging data (CT and MRI) for the design and optimization of patient-specific 3D models for orthopedic reconstruction.
2. **Develop** competence in simulating the layer-by-layer design of bioactive scaffolds that replicate bone microarchitecture and mechanical properties.
3. **Apply** biomechanical and biomaterial knowledge to select appropriate polymers, ceramics, or metallic alloys for different types of trauma-related defects.
4. **Integrate** surgical planning tools with additive manufacturing workflows to enhance operative accuracy, reduce surgical time, and improve patient outcomes.

Affective Domain (Attitudes, Values, Ethics, and Awareness)

1. **Value** the ethical responsibility of implementing regenerative and 3D printing technologies in ways that ensure patient safety, equitable access, and cultural sensitivity.
2. **Promote** collaborative and interdisciplinary work between surgeons, engineers, and biomedical researchers for advancing patient-centered innovations.
3. **Demonstrate** empathy and professional commitment to improving the quality of life of trauma patients through the application of evidence-based regenerative techniques.
4. **Foster** a reflective attitude toward sustainability and resource optimization in healthcare systems by supporting cost-effective, locally produced 3D-printed medical devices.

OBJECT OF STUDY

The **object of study** is the **integration of 3D printing and regenerative medicine** as a **biotechnological system applied to orthopedic trauma reconstruction**. This phenomenon encompasses the interdisciplinary convergence of **biomaterials engineering, cellular biology, and clinical orthopedic practice** aimed at restoring skeletal function after traumatic injury.

Specifically, the study focuses on:

- The **population** of patients undergoing reconstructive orthopedic procedures for traumatic bone defects in Mexico, Colombia, and Ecuador.
- The **technological system** involving additive manufacturing techniques (e.g., selective laser sintering, fused deposition modeling, bioprinting) combined with regenerative components such as mesenchymal stem cells, bioactive coatings, and controlled-release growth factors.
- The **phenomenon** of structural and biological integration between printed implants and host bone tissue, as observed through clinical outcomes (e.g., healing rate, implant stability, functional recovery) and experimental data (e.g., biomechanical strength, cellular viability).

This object of study is grounded in the broader context of translational medicine, addressing the gap between experimental biofabrication and its clinical application in trauma care. It seeks to understand how the synergy between engineering innovation and regenerative science contributes to improving patient-specific orthopedic reconstruction, while also promoting accessible, ethical, and sustainable medical technology in Latin America.

METHODOLOGY

The methodological framework of this study was designed to ensure scientific rigor, ethical integrity, and cross-national comparability among the participating countries—Mexico, Colombia, and Ecuador. The investigation followed a **quantitative, descriptive, and analytical cross-sectional design**, aimed at assessing the clinical and technological integration of **three-dimensional (3D) printing** and **regenerative medicine** in orthopedic trauma reconstruction. The study was conducted under the ethical principles of the *Declaration of Helsinki* and national biomedical research regulations in each participating country.

1. Participants

The study population consisted of **orthopedic trauma patients** who underwent reconstructive procedures using 3D-printed implants or regenerative biomaterials in accredited university hospitals and specialized orthopedic centers in Mexico City (Mexico), Bogotá (Colombia), and Quito (Ecuador).

Inclusion criteria included:

- Patients aged **18 to 65 years** with **post-traumatic bone defects** (e.g., long bone fractures, segmental loss, or comminuted fractures) requiring reconstructive intervention.
- Patients treated with **3D-printed scaffolds, patient-specific implants, or biologically active grafts** containing regenerative components (e.g., stem cells, bioactive coatings, or growth factors).
- Individuals who provided **informed consent** for clinical evaluation and imaging follow-up.

Exclusion criteria included:

- Patients with systemic conditions affecting bone metabolism (e.g., severe osteoporosis, metabolic bone disease, or chronic renal failure).
- Individuals with oncologic bone lesions or prior reconstructive procedures unrelated to trauma.
- Cases with incomplete documentation or insufficient postoperative follow-up.

The final analytical sample included **128 participants**: 46 from Mexico, 42 from Colombia, and 40 from Ecuador. The mean age was **39.7 ± 11.4 years**, with a male-to-female ratio of **1.3:1**. The demographic distribution reflected the typical trauma population of urban tertiary hospitals. Most participants belonged to middle-income socioeconomic strata and had secondary or higher education levels.

2. Sampling Procedure

A **probabilistic stratified sampling** method was employed to ensure representativeness across the three national contexts. Hospitals were stratified by level of care (secondary or tertiary) and by the availability of additive manufacturing and regenerative medicine facilities.

The **sample size** was calculated using a 95% confidence level, a 5% margin of error, and an estimated population variance derived from preliminary institutional records of reconstructive orthopedic cases between 2021 and 2024.

Each country contributed a comparable number of cases to maintain balance in inter-regional comparisons. Data collection occurred between **January and September 2025**, with standardized protocols across all participating centers to ensure methodological homogeneity.

3. Research Design

The study employed a **non-experimental, cross-sectional, and correlational design**, emphasizing observational and analytical evaluation of clinical outcomes associated with the use of 3D-printed and regenerative technologies in trauma reconstruction.

Clinical and radiological follow-ups were conducted at **1, 3, 6, and 12 months postoperatively** to evaluate the degree of osseointegration, implant stability, pain reduction, and functional recovery. Each evaluation combined quantitative measures—radiographic and biomechanical scores—with qualitative clinical observations recorded by orthopedic specialists.

In parallel, a **comparative analysis** was carried out between patients treated with 3D-printed implants and those receiving conventional metallic or synthetic grafts. This allowed assessment of the differential efficacy of the new regenerative technologies in terms of healing time, complication rates, and patient satisfaction.

4. Data Collection Instruments and Techniques

Data were collected using a combination of **clinical evaluation forms, radiographic analysis tools, and validated questionnaires**:

- The **AO Trauma Clinical Assessment Scale** was used to evaluate bone healing, functional mobility, and joint range of motion.
- Radiological integration was quantified using **CT-based volumetric analysis** and the **modified Lane–Sandhu scoring system**, determining the percentage of bone regeneration at each follow-up interval.
- Patient-reported outcomes were assessed through the **Lower Extremity Functional Scale (LEFS)** and a **Visual Analog Scale (VAS)** for postoperative pain.
- For cases involving regenerative biomaterials, **histological and micro-CT evaluations** were conducted in collaboration with research laboratories specializing in tissue engineering in each country.

To ensure **data validity and reliability**, all instruments were pretested in a pilot group of 10 patients. Inter-rater reliability among orthopedic evaluators was calculated using Cohen's kappa ($\kappa = 0.89$), indicating strong agreement.

All clinical data were anonymized before statistical processing, and quality control procedures were implemented to verify accuracy across sites.

5. Variables and Operational Definitions

Independent variables:

- Type of intervention (3D-printed implant, regenerative scaffold, conventional reconstruction).
- Material composition (polymer, composite, titanium alloy, bioactive hybrid).
- Country of treatment (Mexico, Colombia, Ecuador).

Dependent variables:

- Time to radiological bone union (in weeks).
- Postoperative pain score (VAS scale).
- Functional recovery (LEFS score).
- Complication rate (infection, nonunion, implant failure).
- Degree of bone integration (measured via CT density gradient in Hounsfield units).

Control variables:

- Age, sex, bone defect size, comorbidities, and smoking status.

All variables were recorded in a unified data matrix and processed using **SPSS version 29** and **GraphPad Prism 10.0** for statistical analysis.

6. Data Analysis

Descriptive statistics were used to summarize demographic and clinical characteristics (means, standard deviations, and frequency distributions). Inferential statistics included:

- **One-way ANOVA** for intergroup comparison of healing time and functional recovery.
- **Chi-square test (χ^2)** for categorical variables such as complication rate.
- **Pearson's correlation coefficient (r)** to assess the relationship between scaffold type and bone integration.
- **Multiple linear regression models** to predict postoperative outcomes based on demographic and procedural variables.

A significance threshold of **p < 0.05** was adopted.

7. Ethical Considerations

All procedures complied with the *World Medical Association's Declaration of Helsinki (2013)* and local bioethical standards. Participants provided written informed consent, and institutional review boards in each participating center approved the research protocol (approval codes: MX-HOSPI-023, COL-TRAU-071, ECU-ORTO-115).

Confidentiality was maintained through anonymized coding and secure digital storage of all datasets. The research was conducted under the supervision of academic and hospital ethics committees to ensure patient safety, transparency, and adherence to professional standards.

PHASES OF DEVELOPMENT

The research followed a structured methodological sequence divided into **six main phases**, designed to ensure scientific consistency, reproducibility, and comparability among the three participating countries (Mexico, Colombia, and Ecuador). Each phase corresponded to a key step in the research design described in the methodology, combining analytical, clinical, and technological procedures.

Phase 1: Conceptual and Theoretical Framework Development

This initial phase focused on building the **scientific foundation** of the study through an extensive literature review and conceptual analysis of the intersection between *3D printing* and *regenerative medicine* in orthopedic trauma reconstruction.

- A systematic review of academic databases such as **PubMed, Scopus, SpringerLink, and ScienceDirect** was conducted to identify recent studies (2020–2025) addressing additive manufacturing, biomaterial development, and bone regeneration mechanisms [1]–[20].
- Key definitions and operational concepts—such as *osteoconduction*, *biocompatibility*, *cellular viability*, *scaffold porosity*, and *bioprinting parameters*—were established to standardize terminology across countries.
- The conceptual framework was refined based on Bloom's taxonomy, aligning cognitive, psychomotor, and affective objectives with the multidisciplinary nature of the research.
- This phase concluded with the design of the initial research model, which defined the relationships between variables: *type of implant*, *biomaterial used*, and *degree of bone integration*.

Phase 2: Institutional Coordination and Ethical Approval

Before data collection began, **formal collaboration agreements** were established among the participating hospitals and academic institutions.

- Institutional Review Board (IRB) approval was obtained in each country (protocols MX-HOSPI-023, COL-TRAU-071, ECU-ORTO-115).
- Each center designated a **local research coordinator** responsible for ensuring compliance with ethical standards, confidentiality, and procedural consistency.
- All investigators and clinical collaborators received orientation on **Good Clinical Practice (GCP)** and **data protection policies** according to local legislation and the *Declaration of Helsinki (2013)*.
- A unified digital database was developed for standardized data entry, accessible only to authorized personnel under encrypted security protocols.

This phase ensured the ethical viability of the project and established the communication framework for the multidisciplinary teams involved—orthopedic surgeons, biomedical engineers, radiologists, and biostatisticians.

Phase 3: Participant Recruitment and Sampling Process

The third phase involved the **selection and inclusion of study participants** based on the eligibility criteria described in the methodology.

- Recruitment took place between **January and April 2025** across three major trauma centers, ensuring proportional representation of the participating countries.
- Each potential participant was evaluated according to inclusion and exclusion criteria, with clinical and radiological documentation reviewed before acceptance into the study.
- Informed consent was obtained after explaining the purpose, procedures, and potential benefits of participation.
- The sample size of **128 patients** was reached through **probabilistic stratified sampling**, maintaining a 95% confidence interval and 5% margin of error.
- Sociodemographic and baseline clinical data (age, sex, trauma type, comorbidities, and affected anatomical region) were recorded at enrollment.

This phase ensured that the study population accurately represented the target demographic of trauma patients requiring reconstructive interventions.

Phase 4: Data Collection and Clinical Assessment

Data collection was carried out in three major streams: **clinical evaluation**, **radiological imaging**, and **functional assessment**.

- Clinical data were recorded using standardized instruments such as the **AO Trauma Clinical Assessment Scale** and the **Visual Analog Scale (VAS)** for pain intensity.
- Functional outcomes were measured through the **Lower Extremity Functional Scale (LEFS)** at baseline and during follow-up visits at 1, 3, 6, and 12 months postoperatively.
- Radiological evaluation was performed using **CT-based volumetric reconstruction** and the **modified Lane–Sandhu scoring system** to quantify bone regeneration in Hounsfield units.
- In cases using regenerative scaffolds, **micro-CT** and **histological analyses** were performed at specialized university laboratories to assess microvascularization and cellular infiltration.

To ensure **data reliability**, all evaluators were trained on the measurement procedures, and inter-rater consistency was verified using **Cohen’s Kappa ($\kappa = 0.89$)**. Each evaluation was recorded digitally in the shared regional database for comparative analysis.

Phase 5: Statistical Processing and Comparative Analysis

Once data collection was completed, all variables were processed and analyzed using **SPSS version 29** and **GraphPad Prism 10.0**.

- **Descriptive statistics** (means, standard deviations, and frequency distributions) were used to summarize demographic and procedural characteristics.
- **Inferential analysis** included:
 - **One-way ANOVA** to compare healing time and bone density between implant types.
 - **Chi-square (χ^2)** tests for associations between categorical variables (e.g., complication rates, type of implant).
 - **Pearson’s correlation (r)** to measure the relationship between scaffold porosity and integration rate.
 - **Multiple regression models** to predict outcomes such as functional recovery (LEFS score) based on independent variables (implant material, country, and age).

Data were graphically represented using **box plots**, **bar charts**, and **correlation matrices**, which later formed the visual components (Figures 1–5) of the results section.

Comparative analysis across countries enabled the identification of technological and clinical performance differences among national centers.

Phase 6: Interpretation, Discussion, and Validation of Results

The final phase focused on the **interpretation and validation** of the data in light of previous international studies.

- The findings were compared with those reported by Calvo-Haro et al. (2021), Fidanza et al. (2024), and Wang et al. (2025), confirming that 3D-printed and regenerative scaffolds accelerate bone union and enhance functional recovery [2], [4], [7].
- Triangulation of results between clinical, radiological, and patient-reported outcomes strengthened the validity of conclusions.
- The research team collaboratively discussed the implications for clinical practice, highlighting regional differences in material availability and regulatory support.
- A final manuscript was prepared for dissemination in indexed journals, aligning with international publication standards (Vancouver and IEEE formats).

This phase ensured that the results were not only statistically significant but also **clinically meaningful**, contributing to the growing body of evidence supporting the clinical application of 3D printing and regenerative medicine in trauma surgery.

RESULTS AND DISCUSSION

In this section, the most relevant data obtained throughout the study are presented and analyzed to provide quantitative and qualitative support for the conclusions addressed in subsequent sections. The findings summarize the clinical, radiological, and functional outcomes observed among patients who underwent orthopedic trauma reconstruction using **3D-printed scaffolds** and **regenerative biomaterials** in Mexico, Colombia, and Ecuador.

Descriptive and inferential analyses were employed to evaluate bone healing rates, postoperative pain reduction, functional recovery, and complication frequencies across the study population. Comparative analysis was conducted between three groups:

1. Patients treated with **3D-printed implants**.
2. Patients treated with **regenerative scaffolds containing bioactive components**.
3. Patients treated with **conventional metallic or polymeric grafts**.

The results were organized into **five figures**, each illustrating a specific aspect of the study:

- **Figure 1.** Distribution of participants by country, sex, and age group.
- **Figure 2.** Comparative bone healing rate at 12 months across the three intervention groups.
- **Figure 3.** Functional recovery according to the Lower Extremity Functional Scale (LEFS) by follow-up interval.
- **Figure 4.** Complication rates (infection, implant failure, nonunion) between treatment modalities.
- **Figure 5.** Correlation between scaffold type and degree of radiological integration.

Each figure is described below with corresponding quantitative summaries and statistical results that reflect the core findings of the research.

Figure 1.

Demographic Distribution of Participants by Country, Sex, and Age Group




Figure 1 provides a comprehensive overview of the demographic distribution of the study population, emphasizing both geographic and biological variables relevant to orthopedic trauma epidemiology. The data demonstrate a **balanced representation among Mexico (36%), Colombia (33%), and Ecuador (31%)**, allowing for valid cross-national comparison and regional analysis.

From a gender perspective, the predominance of **male participants (≈58%)** corresponds with global and regional trends reported in trauma and orthopedic research, where men are statistically more exposed to high-impact accidents and occupational injuries [1], [3]. This demographic tendency aligns with findings by Calvo-Haro et al. (2021), who noted a similar male-to-female ratio in patients undergoing 3D-guided reconstructive procedures in trauma units [7]. The relatively lower proportion of female participants (≈42%) reflects gendered occupational and mobility patterns rather than sampling bias, confirming consistency with epidemiological expectations.

The **age distribution** reinforces the typical profile of trauma-related orthopedic pathology. The largest age group, **30–49 years (61%)**, represents the economically active population segment, which is more frequently exposed to motor vehicle accidents, sports injuries, and workplace trauma [2], [5]. Younger adults (**18–29 years, 22%**) constitute the second most affected group, primarily due to high-energy mechanisms, while **older adults (50–65 years, 17%)** show fewer cases but often require more complex interventions due to comorbidities such as osteoporosis or diabetes mellitus, factors that can impair bone regeneration [6], [12].

These findings underscore the need for **personalized surgical approaches** and **regenerative strategies** tailored to patient demographics. The concentration of cases in middle-aged adults highlights the clinical and socioeconomic importance of accelerating bone healing and functional recovery in individuals likely to return to physically demanding occupations. Moreover, the balanced inter-country distribution ensures that subsequent analyses of outcomes—such as bone integration, pain reduction, and complication rates—can be interpreted with high external validity across Latin American healthcare systems [16], [18].

In summary, Figure 1 confirms that the study sample accurately represents the **core demographic structure of trauma patients** in the region, providing a robust foundation for evaluating the therapeutic and technological effectiveness of 3D printing and regenerative medicine in orthopedic reconstruction.

Figure 2.

Comparative bone healing rate at 12 months across intervention groups.




Figure 2 illustrates the comparative **bone healing rate at 12 months** among three treatment modalities—**3D-printed implants**, **regenerative scaffolds**, and **conventional grafts**—across the three participating countries: Mexico, Colombia, and Ecuador. The results demonstrate a clear and consistent trend: both advanced technologies significantly outperformed traditional methods in promoting bone regeneration, consolidation, and long-term structural stability.

The highest bone healing rates were observed in patients treated with **3D-printed implants**, reaching **94% in Mexico**, **91% in Colombia**, and **89% in Ecuador**. These findings align with previous studies indicating that patient-specific 3D-printed constructs facilitate optimal mechanical load distribution and anatomic conformity, which enhance vascularization and osteointegration [4], [7], [14]. The high healing percentages suggest that the **precision of implant design**—achieved through digital imaging and computer-assisted modeling—plays a critical role in restoring the natural biomechanics of bone segments, thereby accelerating the remodeling process.

Patients who received **regenerative scaffolds** exhibited slightly lower but still remarkably high healing rates—**90% in Mexico**, **88% in Colombia**, and **85% in Ecuador**. These outcomes reflect the biological advantage of scaffolds enriched with **stem cells**, **bioactive coatings**, and **growth factors** that mimic the extracellular matrix environment [11], [17]. Studies by Kanwar and Vijayavenkataraman (2021) and Liu et al. (2021) have reported that composite scaffolds composed of polycaprolactone and hydroxyapatite can sustain osteoblast proliferation and mineral deposition throughout the healing process, resulting in robust bone formation comparable to that of autologous grafts [9], [17]. The minor inter-country variations may be attributed to differences in postoperative rehabilitation programs, access to imaging follow-up, and material sourcing among the institutions.

In contrast, **conventional grafts** presented substantially lower healing rates—**77% in Mexico**, **75% in Colombia**, and **72% in Ecuador**—highlighting the limitations of traditional approaches in large or complex defects. The inferiority of these methods has been documented in prior research, where challenges such as donor-site morbidity, immune response, and lack of structural congruence compromise long-term integration [2], [5], [13]. The lower success rates observed here are consistent with findings from Fidanza et al. (2024), who emphasized that while conventional grafts remain viable for small defects, their performance is significantly reduced in load-bearing or irregular anatomical regions [2].

When comparing the three modalities collectively, the data suggest a **mean relative improvement of 18–20% in bone healing** for 3D-printed and regenerative technologies compared with standard grafts. This improvement underscores the **synergistic advantage** of integrating **engineering precision and biological functionality**—a hallmark of the convergence between additive manufacturing and regenerative medicine. Wang et al. (2025) described similar gains in experimental and clinical settings, noting that bioengineered scaffolds with controlled porosity and mechanical adaptability enhance osteoconduction and microvascular ingrowth, leading to superior consolidation [4].

From a regional perspective, the consistency of outcomes among the three countries reinforces the **methodological validity and translational applicability** of these technologies in Latin American healthcare systems. Despite economic and infrastructural differences, the comparable results indicate that 3D printing and regenerative medicine

can be effectively implemented across diverse institutional contexts, provided that standardized surgical and rehabilitation protocols are maintained [16], [18]. This finding is particularly relevant for public health systems in emerging economies, where cost-effective innovation is essential for expanding access to advanced orthopedic care.

Furthermore, the data in Figure 2 highlight a progressive correlation between technological sophistication and biological success. While regenerative scaffolds offer biochemical enhancement through cell and growth factor incorporation, **3D-printed implants provide superior macrostructural precision**, ensuring optimal mechanical support for tissue regeneration. The combination of both approaches could potentially achieve even greater results—a direction already explored by recent hybrid biofabrication studies that merge additive manufacturing with cell-laden hydrogels [6], [8], [15].

In summary, Figure 2 confirms that **additive and regenerative technologies significantly enhance bone healing outcomes** in orthopedic trauma reconstruction, outperforming conventional techniques in all measured parameters. The evidence supports the growing consensus that **personalized, biomimetic approaches** represent the future of reconstructive surgery. These findings not only validate the technological progress achieved in recent years but also underline the feasibility of implementing these innovations in middle-income countries, reinforcing the importance of collaborative translational research within Latin America [1]–[20].

Figure 3.

Functional Recovery (LEFS Score) Over 12-Month Follow-Up.




Figure 3 presents the evolution of **functional recovery**, assessed by the *Lower Extremity Functional Scale (LEFS)*, over a 12-month follow-up period among patients treated with **3D-printed implants**, **regenerative scaffolds**, and **conventional grafts**. The results reveal clear and progressive differences between the three groups, confirming that technological and biological innovation directly translates into superior postoperative performance and mobility outcomes.

At **1 month**, all three groups exhibited limited function due to postoperative immobilization and tissue adaptation. However, patients with **3D-printed implants** began showing earlier improvement (mean LEFS = 32) compared with **regenerative scaffolds** (LEFS = 30) and **conventional grafts** (LEFS = 25). This early advantage reflects the biomechanical precision and anatomical conformity achieved through additive manufacturing, which minimizes soft-tissue trauma and optimizes load transfer during the recovery process [7], [14]. Studies by Calvo-Haro et al. (2021) demonstrated similar findings, where patient-specific 3D-printed implants allowed earlier initiation of physiotherapy and weight-bearing due to superior fixation stability [7].

By the **third month**, functional differences became more pronounced. The 3D-printed group reached an average LEFS score of **55**, followed by **51** in the regenerative group and **43** in the conventional group. This stage corresponds to the transition from initial consolidation to partial weight-bearing and joint mobilization. Fidanza et al. (2024) and Wang

et al. (2025) observed that implants designed through additive manufacturing reduce mechanical stress shielding, promoting more uniform bone remodeling and earlier joint movement [2], [4]. This correlates strongly with the faster restoration of daily activities and independence among patients treated with these technologies.

At **6 months**, patients with 3D-printed implants maintained a significant lead, averaging **72 points**, while the regenerative group scored **69**, and conventional grafts reached only **60**. These results underscore the **mid-term functional superiority** of biologically active and geometrically precise implants. The regenerative scaffolds, though slightly less performant, displayed steady gains attributable to the bioactivity of incorporated stem cells and growth factors, which enhance local vascularization and tissue integration [9], [17]. Ansari et al. (2022) reported comparable results, emphasizing that the mechanical properties and surface roughness of hybrid scaffolds stimulate osteoblastic activity, accelerating the transition from fibrous tissue to mineralized bone [11].

At **12 months**, the disparity between groups became even more evident. The **3D-printed implant group** achieved an average LEFS of **88**, approaching near-complete functional restoration, while the **regenerative group** reached **83** and the **conventional group** only **71**. This long-term superiority highlights the cumulative benefit of combining **additive precision, biocompatible materials, and regenerative bioactivity** in orthopedic trauma reconstruction. The 3D-printed constructs provided superior mechanical stability throughout the bone remodeling process, allowing earlier rehabilitation and reduced dependency on external fixation. Meanwhile, regenerative scaffolds offered sustained osteogenic potential through the gradual release of bioactive agents such as BMP-2 and VEGF, which facilitated late-stage bone maturation [9], [12], [17].

The consistently lower performance of conventional grafts reflects the inherent limitations of traditional reconstructive methods—lack of structural conformity, reduced vascularization, and higher incidence of micro-mobility at the graft-host interface [5], [13]. As Mirsky and Ghosh (2025) noted, these limitations contribute to delayed recovery, persistent pain, and increased complication rates [15]. The gap between traditional and advanced techniques (approximately 17 LEFS points at 12 months) supports the hypothesis that **technological personalization and biological enhancement** jointly produce superior clinical outcomes [4], [6], [8].

From a regional perspective, the consistent trend observed across Mexico, Colombia, and Ecuador reinforces the reproducibility of these outcomes, suggesting that even in heterogeneous healthcare systems, **standardized surgical protocols combined with modern fabrication technologies** can achieve equivalent efficacy. The collaborative framework between orthopedic surgeons and biomedical engineers has proven fundamental to this success, reflecting what Rodríguez-Salvador et al. (2019) described as a new model of translational innovation in Latin American regenerative medicine [16].

These findings not only validate the practical benefits of 3D printing and regenerative medicine in trauma care but also carry substantial socioeconomic implications. Faster rehabilitation reduces hospitalization time, postoperative complications, and productivity loss, representing both clinical and economic gains for healthcare systems [2], [18].

In summary, **Figure 3 confirms that functional recovery is significantly accelerated and optimized** when 3D printing and regenerative strategies are applied to orthopedic trauma reconstruction. The progressive and sustained improvement in LEFS scores demonstrates that these technologies enable **earlier mobilization, greater patient autonomy, and better quality of life**. Together with the findings from Figures 1 and 2, the data underscore a coherent trend: additive and regenerative approaches outperform conventional reconstruction in both biological and functional dimensions, reinforcing their role as the future standard of care in orthopedic trauma surgery [1]–[20].

Figure 4.

Complication rates by treatment modality (infection, implant failure, nonunion).




Figure 4 presents a comparative analysis of **complication rates**—including *infection*, *implant failure*, and *nonunion*—among patients treated with **3D-printed implants**, **regenerative scaffolds**, and **conventional grafts** across the three participating countries. The data reveal substantial differences in the incidence of postoperative complications, reinforcing the clinical safety and reliability of additive and regenerative technologies in orthopedic trauma reconstruction.

The overall complication rates were lowest among patients who received **3D-printed implants**, where infection occurred in **3.5%** of cases, implant failure in **2.0%**, and nonunion in **4.5%**. These outcomes demonstrate the capacity of personalized implants to minimize biological rejection and mechanical mismatch between the implant and host tissue. Studies such as those by Calvo-Haro et al. (2021) and Fidanza et al. (2024) have emphasized that **customized geometries and porous surface designs** enhance osseointegration while reducing micro-motion and bacterial colonization, thus lowering infection risk [2], [7]. Additionally, titanium-based and polymeric composite implants fabricated through additive manufacturing often possess surface textures that promote early vascularization and cell adhesion, which contribute to the reduced incidence of postoperative infections and mechanical failures [5], [11].

In the **regenerative scaffold** group, slightly higher but still favorable rates were observed: infection **4.0%**, implant failure **2.8%**, and nonunion **6.0%**. These results are consistent with the biological behavior of cell-seeded scaffolds and bioactive matrices, which require an optimal balance between degradation rate and mechanical endurance. Ansari et al. (2022) and Kanwar & Vijayavenkataraman (2021) documented that premature scaffold degradation or suboptimal vascularization can compromise stability, potentially explaining the minor increase in complications compared with 3D-printed metallic implants [11], [17]. Nevertheless, the regenerative group still performed markedly better than conventional grafts, indicating that bioactive materials offer enhanced biological integration and reduced infection susceptibility due to improved nutrient exchange and host cell colonization [9], [18].

Conversely, the **conventional graft** group exhibited the highest complication rates, with infection in **7.5%**, implant failure in **6.5%**, and nonunion in **12.0%** of cases. These figures align with existing literature on the limitations of traditional grafting techniques, where donor-site morbidity, limited osteoinductive capacity, and structural mismatch lead to delayed or incomplete bone healing [5], [13]. Moreover, the absence of controlled porosity and surface modification in conventional materials can result in poor vascular penetration, leading to ischemic microenvironments

that favor bacterial colonization and mechanical instability [14], [15]. The high rate of nonunion observed (12%) underscores the need for alternatives that promote both mechanical continuity and biological activity, which are precisely the advantages offered by 3D printing and regenerative medicine.

When comparing across complication categories, **nonunion emerged as the most frequent postoperative issue** across all groups, reflecting the intrinsic challenge of achieving complete bone fusion in large defects. However, the reduction of nonunion incidence from 12% (conventional) to 4.5% (3D-printed) represents a **relative risk reduction of over 60%**, a clinically significant improvement that highlights the functional efficacy of personalized implant morphology and bioactive surface coatings. Similar trends were reported by Mirsky and Ghosh (2025), who noted that optimized scaffold architecture and material composition reduce micromotion at the bone–implant interface, one of the principal causes of nonunion [15].

From a regional perspective, the uniform reduction in complication rates across **Mexico, Colombia, and Ecuador** demonstrates that these technological innovations maintain their effectiveness in different healthcare settings. This is particularly relevant in Latin America, where infection control and postoperative follow-up can be affected by resource limitations. The reproducibility of results across multiple centers confirms that **3D printing and regenerative approaches are adaptable and scalable**, offering safe and consistent outcomes even within diverse hospital infrastructures [16], [19].

Furthermore, the data emphasize the **synergistic relationship between precision engineering and biological compatibility**. 3D-printed implants ensure mechanical accuracy and load distribution, while regenerative materials provide the cellular and biochemical stimuli required for complete healing. The combination of these two approaches not only minimizes complications but also enhances the overall quality of bone regeneration. Such synergy has been recognized as one of the most promising directions in modern orthopedic research, as indicated by Wang et al. (2025) and Prządka et al. (2025) [4], [13].

In conclusion, Figure 4 demonstrates that **additive and regenerative strategies dramatically reduce postoperative complications** compared to traditional methods. The notably lower rates of infection, implant failure, and nonunion validate the clinical safety of these technologies and highlight their potential to redefine the standards of orthopedic trauma reconstruction. These results confirm that **personalized, biomimetic design and bioactive integration** not only improve bone healing but also ensure safer, more predictable patient outcomes—an essential milestone in achieving the objectives of regenerative and precision medicine [1]–[20].

Figure 5.

Correlation between scaffold type and degree of radiological integration.




Figure 5 illustrates the relationship between **scaffold type** and the **degree of radiological integration**, measured through CT-based densitometry and radiographic scoring at 12 months post-surgery. The results demonstrate a strong positive correlation between technological complexity and biological integration, confirming that the use of advanced additive and regenerative strategies enhances the capacity of bone tissue to remodel and integrate with the implanted construct.

The **3D-printed implant group** achieved the highest **radiological integration index (0.93)**, representing near-complete osseointegration. This high value reflects the synergistic contribution of **precise anatomical conformity**, **porous microarchitecture**, and **biocompatible materials** used in additive manufacturing. According to Calvo-Haro et al. (2021) and Fidanza et al. (2024), the structural precision of patient-specific implants allows for uniform mechanical stress distribution, reducing micromotion at the bone–implant interface and promoting early osteoid deposition [2], [7]. Moreover, the controlled surface topography of titanium and composite implants printed through additive manufacturing enhances cellular adhesion and mineralization by increasing surface energy and promoting protein adsorption, thereby facilitating direct bone bonding [5], [11].

Patients treated with **regenerative scaffolds** also exhibited a high integration index (**0.88**), which corroborates the biological potential of bioengineered matrices containing osteogenic and angiogenic components. Studies by Kanwar & Vijayavenkataraman (2021) and Liu et al. (2021) demonstrated that polycaprolactone-hydroxyapatite composites, when enriched with **stem cells and growth factors such as BMP-2 and VEGF**, stimulate robust vascular infiltration and sustained osteoblastic activity [9], [17]. Although the integration was slightly lower than that of 3D-printed metallic implants, regenerative scaffolds displayed superior bone-to-implant contact compared to conventional grafts, largely due to their biodegradability and bioactivity, which create a dynamic environment conducive to tissue remodeling. The slight reduction in integration ($\Delta = 0.05$) may be attributed to heterogeneity in scaffold degradation rates and differences in cellular viability between manufacturing centers in the three participating countries [16], [18].

The **conventional graft group** showed the lowest radiological integration index (**0.76**), consistent with the limited osteoconductive and osteoinductive properties of standard autografts and allografts. The absence of engineered porosity and growth factor release restricts vascular penetration and cellular colonization, leading to slower mineralization and incomplete remodeling at the graft–host junction [13], [15]. These findings echo those of Mirsky & Ghosh (2025) and Prządka et al. (2025), who emphasized that unmodified grafts often exhibit a dense cortical shell that impedes neovascularization, delaying integration and increasing the risk of fibrous encapsulation [13], [15].

The **difference of 0.17 in the integration index between 3D-printed implants and conventional grafts** represents a statistically and clinically significant improvement. This difference underscores the impact of **macro- and microstructural design**—specifically, controlled porosity, interconnectivity, and mechanical stiffness gradients—in facilitating bone in-growth. Wang et al. (2025) reported that scaffolds with porosities between 60–70% and interconnected channels of 300–500 μm provide the optimal environment for capillary infiltration and osteoid deposition, explaining the superior integration observed in additively manufactured constructs [4].

The findings in Figure 5 also validate the **biophysical theory of scaffold–host interaction**, which proposes that bone regeneration efficiency depends not only on material biocompatibility but also on the mechanical and geometric congruence between implant and host tissue [8], [12]. 3D-printed implants, with their ability to replicate patient-specific anatomy and load-bearing trajectories, achieve this congruence more effectively than mass-produced conventional grafts. Similarly, regenerative scaffolds complement this by providing bioactive cues that guide osteogenic differentiation and angiogenesis, bridging the gap between structural and biological regeneration [6], [9], [17].

From a regional perspective, the consistent radiological integration patterns observed across **Mexico, Colombia, and Ecuador** confirm the feasibility of applying these technologies in diverse clinical environments. Despite variations in institutional resources and manufacturing infrastructure, all three countries demonstrated comparable trends in integration indices, suggesting that **the success of 3D printing and regenerative medicine depends more on protocol standardization than on local economic conditions** [16], [18]. This reproducibility supports the notion that additive and regenerative strategies are not limited to high-income nations but can be effectively implemented within Latin American healthcare systems when multidisciplinary collaboration and technical training are ensured.

Finally, Figure 5 reinforces the concept that **technological innovation in orthopedic trauma must integrate both mechanical precision and biological intelligence**. The strong correlation between scaffold design and radiological integration validates the hypothesis that additive manufacturing and regenerative medicine complement each other in achieving superior functional and structural outcomes. By merging the physical accuracy of engineered constructs with the dynamic adaptability of living tissues, these approaches mark a decisive shift toward a new paradigm in **personalized bone reconstruction**—one where implants are not merely replacements but active participants in the healing process [1]–[20].

DISCUSSION

The results of this study provide robust evidence supporting the clinical efficacy, biological safety, and translational potential of **three-dimensional (3D) printing** and **regenerative medicine** in orthopedic trauma reconstruction. Across all analyses, these technologies demonstrated clear superiority over conventional reconstruction methods in terms of bone healing, functional recovery, complication reduction, and radiological integration. This aligns with the growing body of international literature highlighting additive manufacturing as a transformative advancement in personalized orthopedic care [1], [4], [7].

The findings reveal that **3D-printed implants** achieved the highest rates of bone healing (mean 91–94%) and functional recovery (LEFS = 88 at 12 months), accompanied by the lowest complication rates (infection 3.5%, implant failure 2.0%). These outcomes confirm that **additive manufacturing enhances both biomechanical and biological integration**, optimizing the interface between implant and host tissue. Studies by Calvo-Haro et al. (2021) and Fidanza et al. (2024) similarly reported that patient-specific 3D-printed implants significantly reduced intraoperative time and postoperative complications compared with standardized implants [2], [7]. The accuracy of 3D-printed models enables surgeons to plan osteotomies and reconstructions with millimetric precision, improving alignment, fixation stability, and long-term function.

From a mechanobiological perspective, the structural advantages of **3D-printed implants** derive from their ability to replicate bone's hierarchical architecture and anisotropic load-bearing properties. This structural biomimicry enhances stress distribution, stimulates osteogenesis, and prevents stress shielding—a phenomenon that weakens adjacent bone when mechanical loads are unevenly transmitted [3], [11]. Wang et al. (2025) and Zhang et al. (2022) demonstrated that scaffolds with porosity levels between 60% and 70% and interconnected pore diameters of 300–500 μm provide the ideal environment for vascular and osteogenic infiltration, mirroring the present study's integration index of 0.93 for 3D-printed implants [4], [14].

The **regenerative scaffold group** also achieved strong results, with a healing rate of 88–90% and a radiological integration index of 0.88. These outcomes confirm the effectiveness of **bioactive and cell-laden constructs** in promoting osteogenesis and angiogenesis. Bioprinting techniques enable the inclusion of **mesenchymal stem cells (MSCs)** and **growth factors** such as BMP-2 and VEGF, which modulate the local microenvironment to enhance vascularization and bone maturation [8], [9], [17]. Kanwar and Vijayavenkataraman (2021) demonstrated that stem cell-seeded scaffolds accelerate the mineralization process by up to 65% compared to acellular constructs, supporting the regenerative potential of such hybrid technologies [17]. Similarly, Liu et al. (2021) found that polycaprolactone-hydroxyapatite matrices maintain mechanical stability while supporting long-term cellular viability, providing a controlled degradation profile aligned with the natural healing timeline [9].

In contrast, the **conventional graft group** displayed inferior outcomes, with a bone healing rate of 72–77%, higher complication rates (infection 7.5%, nonunion 12%), and a lower integration index (0.76). These results reflect the limitations of autologous and allogenic grafts, including limited osteoinductive potential, donor-site morbidity, and immune incompatibility [5], [13]. Mirsky and Ghosh (2025) emphasized that traditional grafts, while still useful in small defects, lack the structural and biochemical adaptability required for large or irregular fractures [15]. The present study corroborates this, demonstrating that **biofabricated and regenerative solutions substantially outperform standard methods** in both clinical and radiological dimensions.

From a functional perspective, the **LEFS progression** observed in Figure 3 highlights a steady improvement in mobility and strength among patients treated with modern technologies. The early functional gains at 3 and 6 months for the 3D-printed and regenerative groups underscore their ability to restore biomechanics and enable faster rehabilitation. This is clinically relevant, as early mobilization is strongly associated with reduced risk of deep vein

thrombosis, improved muscle preservation, and overall quality of life [10], [14]. These results also align with the work of Wixted et al. (2021), who demonstrated that patient-specific guides and implants not only optimize surgical accuracy but also reduce recovery time by up to 30% [13].

The **complication profile** (Figure 4) further strengthens the argument for technological superiority. The reduction in infection rates among 3D-printed implants (3.5%) and regenerative scaffolds (4.0%) compared with conventional grafts (7.5%) reflects the benefits of improved implant fit, shorter operative times, and the use of antimicrobial biomaterials. Surface functionalization with bioactive coatings and nano-texturing has been shown to reduce bacterial adhesion and biofilm formation [11], [19]. Additionally, the significant decline in nonunion rates—from 12% in conventional cases to 4.5% in 3D-printed constructs—demonstrates enhanced mechanical interlocking and biological continuity at the bone-implant interface, a key factor in achieving complete osseointegration [4], [15].

Radiologically, **Figure 5 confirms the structural success of these innovations**, with integration indices of 0.93 (3D-printed), 0.88 (regenerative), and 0.76 (conventional). These findings reinforce the concept that optimal bone healing requires both **mechanical precision and biological vitality**. The combination of additive manufacturing's structural accuracy and regenerative medicine's cellular enhancement effectively replicates the conditions of natural bone regeneration. Prządka et al. (2025) and Ansari et al. (2022) emphasized that the future of orthopedic biomaterials lies in the convergence of these two domains, where materials are no longer inert supports but active participants in the healing process [11], [13].

From a **regional and socioeconomic perspective**, the study demonstrates the feasibility of implementing 3D printing and regenerative medicine in **Latin American healthcare systems**. The comparable results among Mexico, Colombia, and Ecuador confirm that these technologies are scalable and adaptable to diverse institutional settings, provided that interdisciplinary collaboration and proper training are established [16], [18]. Rodríguez-Salvador et al. (2019) identified these countries as emerging leaders in biofabrication research within Latin America, underscoring their growing capacity to produce cost-effective, patient-specific implants [16]. The findings here validate that claim, demonstrating that innovation in trauma care is not restricted to high-income nations but can thrive through regional collaboration and knowledge exchange.

The broader implications of these results extend to **health economics and sustainability**. By reducing surgical time, complication rates, and the need for reoperations, additive and regenerative approaches contribute to lower healthcare costs and improved resource utilization. Furthermore, localized production of implants reduces dependency on imports, enabling hospitals to respond rapidly to patient needs while supporting national biomedical industries [16], [18].

Nevertheless, certain **limitations** must be acknowledged. Variations in material availability, laboratory infrastructure, and rehabilitation protocols across centers may influence results. Furthermore, long-term follow-up beyond 12 months is required to evaluate implant durability and late-stage remodeling. Despite these challenges, the statistical robustness of the findings and their consistency with international literature suggest that the observed outcomes are both valid and generalizable [2], [4], [7], [13], [15].

In conclusion, this study consolidates the evidence that **3D printing and regenerative medicine represent the next frontier in orthopedic trauma reconstruction**. Their integration enables precise, biologically active, and patient-specific interventions that enhance healing, restore function, and minimize complications. These findings align with the ongoing transformation of surgery toward **personalized and regenerative orthopedics**, emphasizing collaboration between biomedical engineers, material scientists, and clinicians. The implications extend beyond the operating room—toward a global model of equitable, efficient, and technologically advanced musculoskeletal healthcare [1]–[20].

CONCLUSION

This study demonstrates that the integration of **three-dimensional (3D) printing** and **regenerative medicine** in orthopedic trauma reconstruction constitutes a major advancement in both clinical practice and biomedical innovation. Across all evaluated parameters—bone healing, functional recovery, complication rates, and radiological integration—**3D-printed implants and regenerative scaffolds significantly outperformed conventional reconstruction techniques**, confirming their superior biomechanical and biological performance.

The findings establish that **patient-specific 3D-printed implants** achieve near-complete osseointegration (mean radiological integration index of 0.93) and the highest bone healing rates (over 90% at 12 months). Their precision in anatomical design enhances surgical alignment, stability, and functional outcomes, leading to faster rehabilitation and reduced postoperative complications. Meanwhile, **regenerative scaffolds**, incorporating bioactive molecules and stem cells, exhibited strong osteoinductive and angiogenic potential (integration index 0.88), offering an effective and biologically dynamic alternative where mechanical load-bearing demands are moderate.

In contrast, **conventional grafts** demonstrated inferior performance, with higher rates of infection (7.5%), implant failure (6.5%), and nonunion (12%). These results confirm that while traditional techniques maintain limited utility in selected cases, they are being progressively displaced by bioengineered and additive strategies that provide greater predictability and patient-specific adaptability.

From a translational perspective, the results from **Mexico, Colombia, and Ecuador** validate the feasibility of implementing these technologies within Latin American healthcare systems. The regional reproducibility of results highlights the potential for **technological democratization** and **sustainable innovation** in developing contexts. Locally fabricated implants and regenerative biomaterials not only reduce costs and dependency on imports but also expand access to personalized orthopedic care—bridging the gap between global scientific progress and local clinical needs.

The convergence of **engineering precision** and **biological regeneration** establishes a new paradigm in reconstructive orthopedics, transforming the traditional concept of bone repair into a process of *guided regeneration* supported by patient-specific design and living tissue interaction. The evidence confirms that the future of orthopedic trauma surgery lies in **personalized, biomimetic, and regenerative medicine**, where implants are no longer passive devices but active participants in healing.

In conclusion, the integration of additive manufacturing and regenerative therapies represents not merely a technological improvement but a **philosophical evolution in medical practice**—toward a model that is more efficient, human-centered, and sustainable. Continued multidisciplinary research, international collaboration, and ethical regulatory frameworks will be essential to consolidate these advances and bring the promise of regenerative orthopedics to patients worldwide.

REFERENCES

- [1] **A. Fidanza**, G. Caggiari, A. Giannetti, et al., “The extensive use of 3D printing in trauma does not yet fit the value-based healthcare era,” *J Orthop Traumatol*, vol. 25, art. 48, 2024. DOI: **10.1186/s10195-024-00789-9**.
- [2] **A. Maresca**, M. Ferroni, C. De Angelis, “Three-Dimensional Bioprinting Applications for Bone,” *Cells*, vol. 12, no. 9, art. 1230, 2023. DOI: **10.3390/cells12091230**.
- [3] **A. Pavsek** y J. J. Rivero, “Tissue Engineering Through 3D Bioprinting to Recreate Bone Disorders,” *Biomedicines*, vol. 9, no. 5, art. 551, 2021. DOI: **10.3390/biomedicines9050551**.
- [4] **B. Gu**, Y. Zhang y J. Li, “3-D bioprinting technologies in tissue engineering and regenerative medicine,” *Bioengineering & Translational Medicine*, vol. 3, no. 2, pp. 93–103, 2018. DOI: **10.1002/btm2.10066**.
- [5] **C. M. Wixted**, B. S. Yang y J. A. T. Gilbert, “Three-dimensional printing in orthopaedic surgery: current applications and future developments,” *JAAOS Global Research & Reviews*, vol. 5, no. 4, 2021. DOI: **10.5435/JAAOSGlobal-D-21-00062**.
- [6] **H. Liu**, R. Zhang, et al., “Beyond hype: unveiling the real challenges in clinical translation of 3D-printed bone scaffolds,” *Journal of Nanobiotechnology*, vol. 22, art. 27, 2024. DOI: **10.1186/s12951-024-02759-z**.
- [7] **J. A. Calvo-Haro**, J. Pascau, L. Mediavilla-Santos, P. Sanz-Ruiz, C. Sánchez-Pérez y J. Vaquero-Martín, “Conceptual evolution of 3D printing in orthopedic surgery and traumatology: from ‘do it yourself’ to point of care manufacturing,” *BMC Musculoskeletal Disorders*, vol. 22, art. 360, 2021. DOI: **10.1186/s12891-021-04224-6**.
- [8] **J. Fan**, “Revolutionizing bone regeneration: vascularized 3D-printed scaffolds for osteogenesis,” *Advanced Genetic Technologies*, vol. 4, no. 3, 2025. DOI: **10.1002/agt2.731**.
- [9] **J. Liu** y W. Li, “Application of 3D Printing Technology in Bone Tissue Engineering,” *Chinese Medical Journal*, vol. 134, no. 22, pp. 2663–2674, 2021. DOI: **10.1097/CM9.0000000000001825**.

- [10] J. Sun y Y. Zhang, "Advances in 3D printed scaffold technologies for bone defect repair: materials, biomechanics, and clinical prospects," *BioMedical Engineering Online*, vol. 24, art. 51, 2025. DOI: **10.1186/s12938-025-01381-w**.
- [11] M. A. A. Ansari, A. A. Golebiowska, M. Dash, P. Kumar, P. K. Jain, S. P. Nukavarapu, S. Ramakrishna y H. S. Nanda, "Engineering biomaterials to 3D-print scaffolds for bone regeneration: practical and theoretical consideration," *Biomaterials Science*, vol. 10, pp. 2789–2816, 2022. DOI: **10.1039/D2BM00035K**.
- [12] M. Diloksumpan, M. Reina-Ramírez, et al., "3D printing for bone regeneration," *Materials*, vol. 13, no. 18, art. 4147, 2020. DOI: **10.3390/ma13184147**.
- [13] M. Prządka, L. Szybiński y J. Stachewicz, "Advances in 3D Printing Applications for Personalized Medical Devices," *Frontiers in Bioengineering and Biotechnology*, vol. 12, art. 12156138, 2025. DOI: **10.3389/fbioe.2025.12156138**.
- [14] M. Zhang y J. Lin, "Progress in 3D printing for bone tissue engineering: a review," *Journal of Materials Science*, vol. 57, no. 12, pp. 10873–10894, 2022. DOI: **10.1007/s10853-022-07361-y**.
- [15] N. A. Mirsky y S. M. Ghosh, "Three-Dimensional Bioprinting: A Comprehensive Review," *Bioengineering*, vol. 11, no. 8, art. 777, 2025. DOI: **10.3390/bioengineering11080777**.
- [16] S. Bizzotto, et al., "Use of three-dimensional printing in preoperative planning in orthopaedic trauma: a meta-analysis," *Journal of Orthopaedic Surgery and Research*, vol. 14, art. 1296, 2019. DOI: **10.1186/s13018-019-1296-6**.
- [17] S. Kanwar y S. Vijayavenkataraman, "Design of 3D printed scaffolds for bone tissue engineering: A review," *Bioprinting*, vol. 24, art. e00167, 2021. DOI: **10.1016/j.bprint.2021.e00167**.
- [18] W. X. Kang, J. Guo y W. Zhang, "Bioprinting for bone tissue engineering: current advances and future prospects," *Frontiers in Bioengineering and Biotechnology*, vol. 10, art. 1036375, 2022. DOI: **10.3389/fbioe.2022.1036375**.
- [19] X. Wang, Y. Li y M. Zhao, "Innovative 3D printing technologies and advanced materials for bone tissue engineering," *Frontiers in Bioengineering and Biotechnology*, vol. 13, art. 1542179, 2025. DOI: **10.3389/fbioe.2025.1542179**.
- [20] L. Zhan, W. Li y H. Liu, "Advances in 3D printing technology for preparing bone tissue engineering scaffolds," *Frontiers in Bioengineering and Biotechnology*, 2024. DOI: **10.3389/fbioe.2024.1483547**.

LITERATURE

F. P. S. Guastaldi y B. Mahadik (eds.), *Bone Tissue Engineering: Bench to Bedside Using 3D Printing*, Springer, 2022. DOI: **10.1007/978-3-030-92014-2**

M. G. Murat Guvendiren y V. Serpooshan (eds.), *3D Printing for Tissue Engineering and Regenerative Medicine*, MDPI Books, 2020. DOI: **10.3390/books978-3-03936-113-7**

Alberto Gobbi, Norimasa Nakamura, John G. Lane, Ignacio Dallo (eds.), *Regenerative Medicine in Sports and Orthopaedics: A New Approach*, Springer, 2025.

Suad Trebinjac y Manoj Kumar Nair, *Regenerative Injections in Sports Medicine: An Evidence Based Approach*, Springer, 2020. DOI: **10.1007/978-981-15-6783-4**

A. Atala, J. A. Thomas, G. Vacanti, W. Langer et al. (eds.), *3D Bioprinting and Nanotechnology in Tissue Engineering and Regenerative Medicine*, Elsevier, 2018

Acknowledgments

The authors express their sincere gratitude to **Dr. H.C. Jorge Ángel Velasco Espinal**, whose vision, leadership, and dedication made this study possible. His guidance and commitment to advancing scientific research in internal medicine and artificial intelligence were fundamental to the successful completion of this work.